Acid cleaning and disinfectant agent.

This acidic, mildly foaming cleaning agent removes stubborn mineral deposits, soot and cement-film, as well as oils and greases from acid resistant surfaces.


Effective against: stubborn lime and calcium deposits, urine, beer, milk, soot, cement-film, and light deposits of oils and greases.

Field of use:

- Industrial cleaning: as a pre-spraying agent; effectively loosens deposits and calcium stainsand others on cement and acid-resistant natural or synthetic stone; Highly effective in cleaning tiled facilities (e.g. bath or shower rooms).
- · Cleaning floors: for removing calcium deposits, cement-film and other stubborn deposits from all acid-resistant hard floor coverings, such as PVC, ceramic tiles, workshop floors, bricks, polyurethane etc. If there is doubt about the surface, a pre-test is strongly recommended. Do not use for cleaning marble!

Product benefits:

- · powerful cleaning action: cleans quickly.
- · Economical in use: very effective at high dilution ratios.
- degree of biodegradability of the components, PE packaging, and the fact that it can be separately processed as waste.



Application:

- Pre-spray method: Alto ActiveAcid can be used neat, but is generally diluted with water in a ratio from 1:3 to 1:10. Once the soil or deposits have been loosened, they are removed with a high-pressure washer. The pre-spray pump should be made of PP or PE material.
- · High pressure cleaners: are the best way to remove soil or deposits after they are presprayed with Alto ActiveAcid, but this product should not be used directly in the high-pressure washer.
- Manual cleaning: Dilute the product 1:5 to 1:50 before applying it. Avoid contact with your skin.
- Do not use on zinc, tin, normal steel, non-ferrous metals, or painted surfaces.

pH value: 1,5 (1% solution in 20° dH tap water)

UN Number: 3264 Class / Packing Group: 8/II

- Standard equipment
- ullet Standard equipment, ullet Supplementary accessories, ullet Mountable equipment



